WE CLAIM:

1. A window unit comprising:

(a) a window frame defining a frame perimeter; and

(b) a window located within the frame perimeter, the window includes a display module adapted to receive a display signal from a display signal source.

2. The window unit of claim 1 wherein, the display module is a liquid crystal display.

3. The window unit of claim 1 wherein, the window is a sash.

4. The window unit of claim 1 wherein, the window is a plurality of sashes and the display module located on or within one of the plurality of sashes.

5. The window unit of claim 1 wherein, the window moves along a horizontal window unit axis.

6. The window unit of claim 5 wherein, the window moves along a horizontal window unit axis and at least a portion of the window extends beyond the frame perimeter.

7. The window unit of claim 6 wherein, the window moves along a horizontal window unit axis and substantially the entire window extends beyond the frame perimeter.

8. The window unit of claim 7 wherein, the window includes a tab that remains within the frame perimeter when substantially the entire window extends beyond the frame perimeter.

9. The window unit of claim 1 further comprising, a speaker element located on or within the window.

10. The window unit of claim 1 wherein, the display module is adapted to receive a digital display signal from the display signal source.

11. The window unit of claim 1 wherein, the display module is adapted to receive an analog display signal from the display signal source.

12. The window unit of claim 1 wherein, the display module is adapted to receive a digital display signal and an analog display signal from the display signal source.

13. A method comprising:

(a) providing a window frame defining a frame perimeter; and

(b) providing a window within the frame perimeter, the window includes a display module adapted to receive a display signal from a display signal source.